
CARPOLY IKRM5611P MATA PREMIUM INTERIOR WALL PAINT

TECHNICAL DATA SHEET

1. Product description:

IKRM5611P is a kind of professional color mixing base paint. It is made of high quality raw materials and adopts advanced production technique. More than thousand colors are available to get through our color system with 4 base paints. ICAR-KRM5611P is a white color base paint for white and very light colors.

IKRM5611T is a light color base paint for light colors. IKRM5611D is a deep color base paint for deep colors and IKRM5611A is a dark color base paint for dark colors.

2. Main Materials:

Acrylic Polymers, Additives, Water, Colorants, etc.

3. Product Features:

Fresh smell
Anti-bacterial and Anti-fungus
Professional colors
Washable
Excellent color retention

4. Product Usage:

It is suitable for indoor decoration.

5. Product Technical Specifications:

- Theoretical application Using Amount: About 14-18m²/L. Actual application area will final depends on painters' application method, concrete flatness and application environment.
- Surface Dry: Less than 30mins(25°C), Actual dry: 7days (25°C)
- Re-coat Time: More than 4 hours (25°C, 50% Relative Humidity)
- Dilution: Add about 20% clean water into the paint and fully stir it before application.

6. Notes for use:

- The surface must be clean, dry and free from wax, grease, mildew, oil and other adhesive sand and plaster. The cement surface should be totally dry before you apply the sealer. Please make sure the PH value of the base material is less than 10 and moisture content rate is less than 10%.
- Application method: Brush, roller or airless spraying. Airless spray will be the best choose and can get the best effect. High efficient, even and flat enough.
- Application environment: Temperature less than 5 °C or humidity more than 85% are not

suitable for application.

- Maintenance Period: more than 7 days(25°C, 50% humidity) If you come across with low and high temperature application, please lengthen the maintenance period accordingly.
- Suggest Coating System:
Interior wall putty applies 2-3 times —IJRD100 Interior wall sealer applies: 1 time —
IKRM5611P applies: 2 times

7. Product Storage:

- Please store this product into a cool, dry and well ventilated place where the temperature should be more than 0°C.
- Please put this product far away from children.

8. Leakage handling:

If you find leakage of this product, please use sand or mud to cover it. Please deal with the leakage according to your country's requirement of the chemical. Do not pour it into the water or sewer directly.