

Teflon sealing tape, 16,5 m



Order data

| | |
|------------|---------------|
| EAN | 9780201379624 |
| Item class | 04A |

Description

These sealants replace hemp, sealing tapes, and pastes, they are resistant to gases, liquids, air, water, oils, hydrocarbons and many chemical products. Complete surface contact ensures a **100% seal**. Unscrewing, or correction of position during assembly can be performed using conventional tools at any time before the sealant hardens. No sealant residues to block filters and valves. Particularly strong, leak-proof, resilient Teflon strip of the highest quality, for all types of threads. Suitable for propane, butane, natural gas, benzene, and fuels. Temperature range

–240 to + 260 °C.

Application:

Depending on the medium, pipework and size of the thread, for use up to approx. 100 bar (individual tests are necessary), at 200°C to max. 16 bar.

Note:

Before applying sealant, clean the threads with general-purpose cleaner.

Technical description

| | |
|-----------|--------|
| Thickness | 0.2 mm |
|-----------|--------|



SEVER

ПРОФЕССИОНАЛЬНАЯ ТЕФЛОНОВАЯ ЛЕНТА

www.sever-fix.ru

| | |
|--|-------------------------------|
| Width | 19 mm |
| for thread types | All |
| Manufacturer's designation | FF |
| Working life after date of manufacture | 60 mo |
| Length | 16 m |
| Storage temperature | 20 °C |
| Colour | Yellow |
| Operating temperature range | -240 - 260 °C |
| Chemical basis | Polytetrafluorethylene (PTFE) |
| Characteristics | does not stick |
| Characteristics | non-flammable |
| Characteristics | does not become brittle |
| Product name attribute | 12 m |
| Type of product | Sealing strip |