

# BATTERY-BOX PREMIUM HVS

- Capable of High-Powered Emergency-Backup and Off-Grid Functionality
- Highest Efficiency Thanks to a Real High-Voltage Series Connection
- The Patented Modular Plug Design Requires no Internal Wiring and Allows for Maximum Flexibility and Ease of Use
- Cobalt Free Lithium Iron Phosphate (LFP) Battery: Maximum Safety, Life Cycle, and Power
- Compatible with Leading 1 and 3 Phase High Voltage Battery Inverters
- Two Distinct Modules to Cover the Complete Range of System Sizes
- Highest Safety Standards like VDE 2510-50



## BATTERY-BOX PREMIUM HVS

One Battery-Box Premium HVS is composed of 2 to 5 HVS battery modules that are connected in series to achieve a usable capacity of 5.1 to 12.8 kWh.

Additionally, direct parallel connection of up to 3 identical Battery-Box Premium HVS allows a maximum capacity of 38.4 kWh.

Ability to scale by adding HVS modules or parallel HVS stacks later.




## FLEXIBLE, EFFICIENT, SIMPLE



**Internal Plug Connection**  
No Additional Wiring Required



**5.1 - 66.2 kWh**  
Tailored Sizing for Each Application







**Extend Anytime**  
Easily Adapts to New Requirements



**High Power**  
Power for Every Application

## TECHNICAL PARAMETERS **PREMIUM HVS**

				
	<b>HVS 5.1</b>	<b>HVS 7.7</b>	<b>HVS 10.2</b>	<b>HVS 12.8</b>
Battery Module	HVS (2.56 kWh, 102.4 V, 38 kg)			
Number of Modules	2	3	4	5
Usable Energy [1]	5.12 kWh	7.68 kWh	10.24 kWh	12.8 kWh
Max Output Current [2]	25 A	25 A	25 A	25 A
Peak Output Current [2]	50 A, 5 s	50 A, 5 s	50 A, 5 s	50 A, 5 s
Nominal Voltage	204 V	307 V	409 V	512 V
Operating Voltage	160~240 V	240~360 V	320~480 V	400~600 V
Dimensions (H/W/D)	712x585x298 mm	945x585x298 mm	1178x585x298 mm	1411x585x298 mm
Weight	91 kg	129 kg	167 kg	205 kg

### HVS

Operating Temperature	-10 °C to +50°C
Battery Cell Technology	Lithium Iron Phosphate (cobalt-free)
Communication	CAN/RS485
Enclosure Protection Rating	IP55
Round-trip Efficiency	≥96%
Certification	VDE2510-50 / IEC62619 / CEC / CE / UN38.3
Applications	ON Grid / ON Grid + Backup / OFF Grid
Warranty [3]	10 Years
Compatible Inverters	Refer to BYD Battery-Box Premium Inverter Compatible List and Minimum Configuration List

[1] DC Usable Energy, Test conditions: 100% DOD, 0.2C charge & discharge at + 25 °C. System Usable Energy may vary with different inverter brands

[2] Charge derating will occur between -10 °C and +5 °C

[3] Conditions apply. Refer to BYD Battery-Box Premium Limited Warranty Letter.



**BYD Company Limited**  
[www.byd.com/energy](http://www.byd.com/energy)  
 Global Sales: [batteryboxgrp@byd.com](mailto:batteryboxgrp@byd.com)  
 Global Service: [bboxservice@byd.com](mailto:bboxservice@byd.com)

**Battery-Box EU Service Partner**  
 EFT-Systems GmbH  
[www.eft-systems.de](http://www.eft-systems.de)  
[info@eft-systems.de](mailto:info@eft-systems.de)

**Battery-Box AU Service Partner**  
 Alps Power Pty Ltd  
[www.alppower.com.au](http://www.alppower.com.au)  
[service@alppower.com.au](mailto:service@alppower.com.au)

**Battery-Box US Service Partner**  
 EFT-Systems GmbH  
[www.eft-systems.de/us](http://www.eft-systems.de/us)  
[USservice@eft-systems.de](mailto:USservice@eft-systems.de)

v1.0

