

| Model | | LST48 |
|----------------------------------|---------|---|
| | | Refrigerator |
| Capacity | liter | 372 |
| | cu. ft. | 13 |
| Exterior Dimension | mm | 1227 x 762*1 x 1082*2 |
| (W x D x H) | inch | 48.4 x 30*1 x 42.6*2 |
| Packing Dimension (W x D x H) | mm | 1263 x 865 x 1099 |
| | inch | 49.7 x 34.1 x 42.3 |
| Net Weight | kg | 100 |
| | lb | 222 |
| Packing Weight | kg | 126 |
| | lb | 280 |
| No. of Casters | | 4 |
| No. of Shelves | | 2 |
| Door | | 2 Swing Doors |
| Pan | | 12 (1/6 Size) |
| Compressor (hp) | | 1/3 |
| Refrigerant | | R-134a |
| Range of Temperature | | 0~4 °C / 32~40 °F |
| Voltage / Frequency | | 115 V / 60 Hz 220~240 V / 50 & 60 Hz |
| Rated Input (A/W, 115V 60Hz) | | 5.5 A / 500 W |
| Rated Input (A/W, 220~240V 50Hz) | | 2.5 A / 400 W |
| Rated Input (A/W, 220~240V 60Hz) | | 2.5 A / 400 W |
| Defrosting | | Auto |
| Certification | | Safety - UL Sanitation - UL CE |



LST48 (Refrigerator)

Sandwich & salad prep table, Refrigerator, Two-section, 13.1 cu. ft., Stainless steel inside and outside, 4" caster, Adjustable shelves, Rear mount compressor, 1/5 HP, 115 V / 60 Hz, 220~240 V / 50 & 60 Hz, Auto defrosting system Technical Features Partition that prevents food from falling inside the unit Efficient refrigeration system High-density polyurethane insulation