

| Model | | LUCR36 |
|----------------------------------|---------|---|
| | | Refrigerator |
| Capacity | liter | 270 |
| | cu. ft. | 10 |
| Exterior Dimension | mm | 923 x 762*1 x 912*2 |
| (W x D x H) | inch | 36.4 x 30*1 x 35.9*2 |
| Packing Dimension (W x D x H) | mm | 959 x 865 x 929 |
| | inch | 37.8 x 34.1 x 36.6 |
| Net Weight | kg | 74 |
| | lb | 164 |
| Packing Weight | kg | 91 |
| | lb | 202 |
| No. of Casters | | 4 |
| No. of Shelves | | 2 |
| Door | | 2 Swing Doors |
| Compressor (hp) | | 1/5 |
| Refrigerant | | R-134a |
| Range of Temperature | | 0~4 °C / 32~40 °F |
| Voltage / Frequency | | 115 V / 60 Hz 220~240 V / 50 & 60 Hz |
| Rated Input (A/W, 115V 60Hz) | | 3.5 A / 330 W |
| Rated Input (A/W, 220~240V 50Hz) | | 2.0 A / 250 W |
| Rated Input (A/W, 220~240V 60Hz) | | 2.0 A / 250 W |
| Defrosting | | N/A |
| Certification | | Safety - ETL Sanitation - ETL CE Energy Star |



LUCR36 (Refrigerator)

Undercounter, Refrigerator,
Two-section, 9.5 cu. ft.,
Stainless steel inside and outside,
4" caster, Adjustable shelves,
Rear mount compressor,
1/5 HP, 115 V / 60 Hz, 220~240 V / 50 & 60 Hz

Technical Features
Removable evaporator
Energy-saving hot pipe
High density polyurethane insulation
Drawer option available