

| Model                            |         | LUCR48  |
|----------------------------------|---------|---|
|                                  |         | Refrigerator  |
| Capacity                         | liter   | 372   |
|                                  | cu. ft. | 13  |
| Exterior Dimension               | mm      | 1227 x 762*1 x 912*2                                  |
| (W x D x H)                      | inch    | 48.4 x 30*1 x 35.9*2                                  |
| Packing Dimension<br>(W x D x H) | mm      | 1263 x 865 x 929                                      |
|                                  | inch    | 49.7 x 34.1 x 36.6                                    |
| Net Weight                       | kg      | 87  |
|                                  | lb      | 193   |
| Packing Weight                   | kg      | 111   |
|                                  | lb      | 247   |
| No. of Casters                   |         | 4   |
| No. of Shelves                   |         | 2   |
| Door                             |         | 2 Swing Doors   |
| Compressor (hp)                  |         | 1/5   |
| Refrigerant                      |         | R-134a  |
| Range of Temperature             |         | 0~4 °C / 32~40 °F                                     |
| Voltage / Frequency              |         | 115 V / 60 Hz<br>220~240 V / 50 & 60 Hz               |
| Rated Input (A/W, 115V 60Hz)     |         | 3.5 A / 330 W   |
| Rated Input (A/W, 220~240V 50Hz) |         | 2.0 A / 250 W   |
| Rated Input (A/W, 220~240V 60Hz) |         | 2.0 A / 250 W   |
| Defrosting                       |         | N/A   |
| Certification                    |         | Safety - ETL<br>Sanitation - ETL<br>CE<br>Energy Star |



## LUCR48 (Refrigerator)

**Undercounter, Refrigerator,  
Two-section, 13.1 cu. ft.,  
Stainless steel inside and outside,  
4" caster, Adjustable shelves,  
Rear mount compressor,  
1/5 HP, 115 V / 60 Hz, 220~240 V / 50 & 60 Hz**

### Technical Features

**Removable evaporator  
Energy-saving hot pipe  
High density polyurethane insulation  
Drawer option available**