

ASD01-Servo



Application

Used for dosing of all kinds of powder products. Usually equipped with a VFFS machine.

Features

- **Independent agitator** in the feeding hopper.
- **Up to 15-30 doses per minute**, depending on the dosing range.
- **Touch Screen control** directly from the packaging machine.
- Interchangeable **dosing screws** for different dosing ranges.
- **Servo motor** for finer adjustment and smooth movement of the dosing screw, which leads to increased dosing accuracy.
- Light and reliable **elevating mechanism**, which makes the cleaning and screw changing fast and easy.
- Improved **safety system**.
- **Vibrational feeding channels** with no wearing parts.

Suitable products:

Ground spices



Chemicals



Supplements



Ground coffee



And many others...

Technical specifications:

| | |
|---------------------------------|--------------------------------------|
| Construction | Stainless steel AISI 304 |
| Productivity/hannels | Up to 15-30 doses per minute |
| Overall dimensions in mm(L*W*H) | 820*830*1140 |
| Weight | 100kg |
| Control | Touch Screen (from the VFFS machine) |
| Drive | Servo motor |
| Electrical supply | 220V±10% from the packaging machine |
| Installed power | 750W |
| Dosing range | In range 1-2000gr. (on requirement) |
| Weighing precision | ±1gr. according to the product |