

ATD-G-series for granular and grain products



**Application**

Used for dosing and packaging of granular and grain products. Usually equipped with a VFFS machine, but could also be used as a standalone filling station.

**Features**

- **Version with 2, 4 and 6 heads.**
- **Up to 50 doses per minute**, depending on the heads number.
- Intuitive control via **Touch Screen**.
- Easy and **inexpensive maintenance**.
- **Stainless steel construction**, according to the safety requirements for working with food products.
- Option for creating **up to 20 preset programs** for the different products, which makes the product switching fast and easy.
- **Double speed vibrational feeding**- fast speed for maximum productivity switches to a slower speed- for maximum accuracy.
- **Vibrational feeding channels** with no wearing parts.
- Capability of **mixing up to 4** different products.

Suitable products:

Sugar and salt



Coffee beans



Pulses



Nuts



*And many others...*

Technical specifications:

Construction	Stainless steel AISI 304
Productivity 2/4/6 channels	Up to 15/30/50 doses per minute
Overall dimensions in mm(L*W*H)	850*800*800 (2/4), 1050*850*1050 (6-ch.)
Weight of 2/4/6- channel weigher	80/100/130kg
Control	Touch Screen
Drive	DC motors, vibrators
Electrical supply	220V±10% from the packaging machine
Installed power	500W
Dosing range	In range 10-1000gr. (on requirement)
Weighing precision	±1gr. according to the product